



Wireless BroadWeigh handheld for viewing an unlimited number of modules, providing an 8 digit LCD reading



User Benefits

- Roams between device in range
- Automatically wakes shackles
- Auto shutdown
- Rugged construction

Ideal Application

- Theatre & Events
- Outdoor Events
- Concerts
- Conferences / Trade Shows


Introduction

The handheld is a portable battery-powered roaming device which allows the viewing of an unlimited number of acquisition modules.

By simply being in range of BroadWeigh shackles, the handheld can wake each device and display the data tag of the BroadWeigh shackle on the LCD display.

Specification at a Glance

- Wakes and reads unlimited numbers of acquisition modules
- Worldwide licence exempt 2.4 GHz radio
- 800 m (2600 ft) range maximum
- Simple configuration via PC using base station with BroadWeigh Toolkit software
- Remote battery check
- Environmentally sealed to IP65 / NEMA 4 dimensions 90 x 152 x 34 mm



Related Products



BW-WSS
Wireless wind speed sensor



BW-S325 & BW-S475 Shackles
BroadWeigh wireless
Crosby Safety Bow Shackles



BW-BSue
Extended range wireless radio
telemetry USB base station



BW-AR
Active repeater to extend
wireless range or coverage

Related Software



BW-Toolkit
Software used to calibrate and
configure your devices



BW-LOG100
Free data logging software package
for advanced monitoring of up to
100 channels

Case Study

The Application:

The weight of large pieces of scenery is often hard to predict due to the various materials that they can be constructed from; similarly the weight of cloths and curtains once painted can be hard to estimate. This can make shipping entire sets of scenery difficult as the total weight is unknown, often leading to the overloading of bars and transport lorries.

The Solution:

A simple BroadWeigh pack featuring a single shackle and handheld display allows carpenters and scenery builders to suspend and weigh items from a single point up to 4750 kg.

The handheld displays the weight of the item suspended to the nearest kg, additional shackles can be added to the system for items that require more than one hanging point.

A single handheld can read from any number of shackles.



CE & Environmental

Storage temperature	- 40 to +85°C
Operating temperature	- 40 to +85°C
Relative humidity	95% maximum non condensing
IP Rating	IP65 / NEMA 4

CE Environmental Approvals

European EMC Directive	2004/108/EC
Low Voltage Directive	2006/95/EC

For more information contact us today...

www.broadweigh.com
info@broadweigh.com
Devon, EX5 2JB, UK
T: +44 (0) 1395 232020
F: +44 (0) 1395 233190



In the interests of continued product development, Mantracourt Electronics Limited reserves the right to alter product specifications without prior notice